



BETON-FIX®

DESCRIPTION

BETON-FIX is a powder product ready to use, it is a mixture of selected sands, cement, dispersant and plasticizers agents, powder resin.

It can be used for :

- As a clinging mortar between concrete casts
- Repair cracks or level existing concrete floors.
- As a clinging mortar to realize Chromostone floors on existing concrete.
- Restoration of damaged industrial floorings
- Restoration of construction, shrinkage and expansion joints
- Restoration of holes, cracks, lines due to pipes or other facilities.

CARATTERISTICS

- High adhesion on cement surfaces
- High superficial strength
- High tear resistance
- Waterproof and breathable (it permit to vapour to exit from fresh cement surfaces)
- Free from chlorides, sulphates and carbonates.

APPLICATION

Clean well the existing concrete surface and be sure that it is resistant and solid; All surfaces must be free of oils, grease, dirt, mildew, paint, curing agents and anything that will prevent the product from adhering to the surface plus it must rough and porous.

Wet the surface before applying the Beton-Fix, use a brush to spread the water Mix the product with 6-7 litres of water and apply the mixture with a brush or with a hard bristle brush

YIELD: Mq. 10 per bag.

IMPORTANT: soon after the BETON-FIX application place the next layer (concrete, CHROMOSTONE or whatever) do not let BETON-FIX dry. If occur that the applied BETON-FIX dries apply another coat of it.



PACKAGING

25 Kg paper bags

Store in a dry place on wood pallet .

It's efficient life is about 6 months.

WARNINGS

The product it contains cement, it does not contain any toxic or irritating substance. During working sections the use of anti dust mask and protective gloves is mandatory.

IMPORTANT:

What's in this data sheet is based on best knowledge derived from practical experience and laboratory. This document cancels and replaces the previous ones. The data can be modified at any time. The customer has the responsibility to verify that the product is suitable for the application they want to perform. The manufacturer assumes no responsibility for the results of incorrect applications. It is strongly recommended to test the product on a small area before application. The product is for professional use. The International Stone regularly organizes training courses for its customers who request it. Those who use these products without being entitled do so at their own risk.

Updated on: 25/03/2009