



DECOWAX

DESCRPTION

Waterproofing product, colouring and protective to use up covering by DECOWALL and ROCKWALL.

MANUFACTURE

Can be furnish in color neutral or in varied color between theirs can be mixed for obtain nuance and wished effect chromatic.

Come provide in confections by kg 0,500- kg 3,00- kg 13,00.

Produce around Mq. 15-20 by kg.

APPLICATION

Dilute with our liquid release that use to stamp the DECOWALL.

Apply with brush or sponge after 4-5 days by pose of DECOWALL.

Consult to apply a first coat of DECOWAX neutral on all surface e after intervene with colored Decowax.

WARNING

Since the DECOWAX to contain diluent, during his application in close environmental to aerate locales; after 2 or 3 hours the diluent is completely evaporated and therefore the obtained covering is totally free by toxicity.

IMPORTANT:

What's in this data sheet is based on best knowledge derived from practical experience and laboratory. This document cancels and replaces the previous ones. The data can be modified at any time. The customer has the responsibility to verify that the product is suitable for the application they want to perform. The manufacturer assumes no responsibility for the results of incorrect applications. It is strongly recommended to test the product on a small area before application. The product is for professional use. The International Stone regularly organizes training courses for its customers who request it. Those who use these products without being entitled do so at their own risk.

Updated on:12-06-09