



STONE SPRAY

DESCRIPTION

Stone spray can be applied to cover and decorate horizontal and vertical surfaces made of concrete, plaster, walls made of bricks, laterogesso, concrete bricks etc.

Can be applied on driveways, patios, sidewalks, stairs, swimming pool edges and interior, vertical surface and more.

It's easy to clean with a water shotblaster and, when necessary, with products normally found in stores.

PRODUCTS

The Stone Spray can be used with the following products:

Stencil paper: unique paper that allows to decorate, with fixed drawings, surfaces to be treated.

Hardstone spray: product composed of quartz sand within an appropriate grading curve, white and gray cements, colored pigments, hardening and leaching resins

Stone polymer: Single component composed by various resins which will cause the mortar to stick to the bases in a strong and permanent way.

Sealfloor 100: A resin composed by particular acrylic co-polymers, transparent and very fluid so that it penetrates well in the previously prepared surface against permeability and resistant to oils, greases salts, chlorine, freezing etc.

DIRECTIONS

Concrete must be perfectly dry. All surfaces must be free of oils, grease, dirt, mildew, mould, varnish, and anything that will prevent adherence to the surface. Surfaces should also be degreased with a commercial grade degreaser or scrubbed with a diluted acid, and rinsed abundantly with water. Mix 1 part of STONE POLYMER with to parts of water and use about 7 litres of this mix per bag of HARDSTONE SPRAY.

Moist the surface without exaggerating and apply a thin coat with a squeegee or trowel and allow to dry.

Once first coat has dried, you can put stencil paper down and make the desired design. After tape is secured, apply the second coat of HARDSTONE SPRAY with a hopper gun for about 2-3 mm. this surface finish can be left that way or can be



worked with a pool trowel in a circular motion. Peel stencil paper before the second coat is too dry and finish off where necessary.

Allow to dry for 48 hours and seal with 2 coats of SEALFLOOR 100.

PACKAGING

STONEPOLYMER: 5-20 litres container

HARDSTONE SPRAY: 25 kg bag

SEALFLOOR 100: 20 litres container

QUALITY

We hereby certify that this product is prepared in accordance with the international standards, is continuously tested in appropriate laboratories and checked prior any shipment; it is therefore a “GOOD QUALITY” Product.

IMPORTANT:

What's in this data sheet is based on best knowledge derived from practical experience and laboratory. This document cancels and replaces the previous ones. The data can be modified at any time. The customer has the responsibility to verify that the product is suitable for the application they want to perform. The manufacturer assumes no responsibility for the results of incorrect applications. It is strongly recommended to test the product on a small area before application. The product is for professional use. The International Stone regularly organizes training courses for its customers who request it. Those who use these products without being entitled do so at their own risk.

Updated on: 12-06-09